

Township of Spring Curb / Sidewalk / Driveway Apron Application

| Applicant's Name | PI | none No |
|--|---------------------|-----------------------|
| Applicant's Address | A | Applicant's email |
| | | Owners Phone No. |
| Owners Address | | |
| | | |
| Location of proposed work | | |
| Type of Work: | New | Replacement \square |
| | | |
| Type of Work: Sidewalk | ☐ Curbing ☐ | Driveway Apron 🗌 |
| 1. Area of work?sq. ft. | 2 . Widthft. | 3. Lengthft. |
| 4. Thickness of concrete? in. 5. Compressive strength of concrete?psi | | |
| 6. Thickness of stone base?in. 7. Reinforcement \square | | |
| Project Narrative, please describe the work to performed: | | |
| | | |
| | | |
| | | |
| Sidewalk Construction Notes | | |
| The minimum width of sidewalk shall be 4 feet unless otherwise specified. A grass area shall separate the sidewalk from the curb unless otherwise specified. The stone base for sidewalks shall be a minimum 4 inch depth of 2B Stone except for sidewalks within driveways the depth shall be 6 inches of 2b stone. The minimum thickness of concrete shall be 4 inches except for sidewalks within driveway areas which shall be 6 inch depth of concrete with two layers of welded wire mesh or concrete shall be 8 inches thick with no wire mesh. | | |
| Driveway Entrance Construction Notes | | |
| Driveway entrance shall have the outside edge raised 1-1/2 inches above the flow line of the gutter. Entrances to public streets shall have a minimum 6 inch 2b stone base, 6 inches of concrete with 2 layers of welded wire mesh or be 8 inches of concrete with no wire mesh. Residential Driveway entrances shall be a minimum of 10 feet wide and be no wider than 20 feet at the right of way of the public road. Residential driveway entrances shall be of the depressed curb-ramp type. No material shall be placed in the cartway adjacent to the curb and entrance area which shall in anyway impede the flow of storm water. | | |
| <u>Curb Construction Notes</u> | | |
| Curb replacement to be of the vertical type or to match the existing curb. Curbs are to have a minimum of 4 inch depth of 2b stone base. | | |
| All Concrete shall have a minimum compressive strength of 3,500 psi. | | |
| Please visit the Township website at www.Springtwpberks.org for additional information regarding Curb/ Sidewalk Specifications. | | |
| The Applicant Certifies that all the information given is correct and that all Township Ordinances will be complied with. | | |
| Applicant Signature | Date | _ Approved |

Denied _____

Permit Fee ______ Issue Date _____

Location of Improvements

Please indicate on the graph paper below the location of the proposed work. Be sure to include property lines, roads, curbs and sidewalks.

