



Permit No. _____

Township of Spring Driveway Application

Version 8-21-2015

Applicant's Name _____ Phone No. _____

Applicant's Address _____ Applicant's email _____

Property Owners Name _____ Owners Phone No. _____

Owners Address _____

Location of proposed Work _____

Type of Work: New Driveway Widen Existing Driveway Replace Driveway Apron

Type of Work: Residential Commercial Industrial

Driveway Apron Section

1. Width _____ ft. (Residential: 10' min, 20' max) 2. Length _____ ft. 3. Area of work? _____ sq. ft.
4. Thickness of concrete? _____ in. 5. Compressive strength of concrete? _____ psi
6. Thickness of stone base? _____ in. 7. Reinforcement YES NO
8. For New Driveways, What is the angle of the intersection with the street? _____ (75° min, 105° max)
- Maximum Grade at driveway Entrance _____ (5% max, first 20 feet)
- Maximum Grade after driveway entrance _____ (12% max)

Driveway Section

1. Width _____ ft. 2. Length _____ ft. 3. Area of work? _____ sq. ft.
4. Type of Material: Concrete Asphalt Other _____

Driveway Entrance Construction Notes

Driveway entrance shall have the outside edge raised 1-1/2 inches above the flow line of the gutter. Entrances to public streets shall have a minimum 6 inch 2b stone base, 6 inches of concrete with 2 layers of welded wire mesh or be 8 inches of concrete with no wire mesh. Residential Driveway entrances shall be a minimum of 10 feet wide and be no wider than 20 feet at the right of way of the public road. Residential driveway entrances shall be of the depressed curb-ramp type. No material shall be placed in the cartway adjacent to the curb and entrance areas which shall in anyway impede the flow of storm water. The stone base for sidewalks within driveways shall be a depth of 6 inches of 2b stone. The minimum thickness of concrete shall be 6 inches of concrete with two layers of welded wire mesh or concrete shall be 8 inches thick with no wire mesh.

All Concrete shall have a minimum compressive strength of 3,500 psi.

Please visit the Township website at www.Springtwpberks.org for additional information regarding Driveway Apron/ Sidewalk/ Curb Specifications.

*** Plot Plan required showing the location of the improvements. See page 2 of application. Driveways to be setback a minimum of 2 feet from property lines unless shared by an adjacent house.**

The Applicant Certifies that all the information given is correct and that all Township Ordinances will be complied with.

Applicant Signature _____ Date _____ Approved _____

Permit Fee _____ Issue Date _____ Denied _____

Location of Improvements

Please indicate on the graph paper below the location of the proposed work. Be sure to include property lines, roads, curbs and sidewalks.

